


Smart IP video Intercom Doorbell

SPARKELEC SVD004BK



Key features	Picture
<ul style="list-style-type: none"> 2MP HD smart IR camera Viewing angle 125° Support web configuration Onvif / RTSP Compatibility Support Exit Button Support Door Contact Input Support swiping card unlock Support password unlock Dual Relay Control (Door/Gate) Surface mounting Protection grade: IK07; IP65 Power over Ethernet (PoE) / DC15V 0.8A 	

Specifications	
Apartments	1
Operation system	Embedded linux
Angle of view	H:125°, V:72°
Video compression standard	H.265 (default), H.264
Noise reduction	3D noise reduction
Night vision	Smart IR
Video frame rate	Main stream: 1920x1080p, 720p, Sub stream: 640x360
Audio intercom	Full duplex
Network interface	10M / 100M adaptive belt POE
Network protocol	TCP/IP, RTSP
Gate	NO/NC (MAX AC/DC30V 4A)
Output unlocking	NO: MAX DC12V 160mA (Transient current: 700mA-40ms)
Wiegand 26/34 output	Set via an indoor monitor
Exit button	Support
Door contact input	Support

Tamper alarm	Support
RFID	13.56MHZ/Mifare/Supports ISO/IEC 14443 type A 106kb/s
	Number of cards supported: 1000
	Card reading distance: ≤2cm
Protection grade	IK07; IP65
Power supply	POE IEEE 802.3af / DC15V, 0.8A
Power consumption	≤3W (Standby), ≤4.5W (Working)
Working temperature	-30°C to +60°C (-22°F to +140°F)
Working humidity	10%RH – 90%RH (non-condensing)
Product size	162x82x29mm

Typical Application

